

Hidrofoare

Hidrofor	BAR JET 80/24	BAR JET 100/24
Putere motor	0,80 kw	1,10 kw
Debit maxim	42 l/min	52 l/min
Adancime de tragere	9 m	9 m
Distanta de impingere	40 m	50 m
Capacitate vas expansiune	24 l	24 l



Vas expansiune hidrofor

24 l
36 l
50 l



Membrana hidrofor

24 l
36 - 50 l



Presostat mecanic hidrofor

1/4"



Racord hidrofor cu 5 cai



Electropompa pentru apa curata

Model	BAR JET 80S
Putere motor	0,80 kw
Debit maxim	46 l/min
Adancime de tragere	9 m
Distanta de impingere	45 m
Temperatura maxima a apei	50°C



Pompa submersibila

Model	BAR CSP 400	BAR CSP 750
Putere motor	400 w	750 w
Debit maxim	7500 l/h	12500 l/h
Adancime de tragere	7 m	7 m
Diametru teava	1", 1 1/4", 1 1/2"	1", 1 1/4", 1 1/2"



Unitate control presiune apa

Model	EVP EPC 1
Voltaj	220V - 240V
Frecventa	50/60 Hz
Temperatura maxima a apei	60°C
Presiune maxima	10 bar

